

SEMI AUTOMATIC CRIMPING MACHINE



WHS2000



※Photo: Machine is equipped with option

Suitable for seal insertion crimping of multi-conductor cable.

Feature

- Setup of strip length and the depth, seal insertion position, crimping position, crimp sink and timing is possible to set at operation panel.
(Multilingual touch panel)
- Preparing options, such as crimping force device, manual application exchange equipment , Other brand APL conversion KIT.
- Bad part cutter (Wire chopper) to cut off defective products. (Options)

SPECIFICATIONS

Model	WHS2000
Functions	Stripping , Crimping , Seal insertion.
Capacity	Single-end stripping and crimping : 1.8sec/pcs. Single-end seal insertion crimping : 2.1sec/pcs.
Wire size	0.13~2.0mm ² (AWG#26~#14)
Wire cutting length	More than 80mm
Tip length	29mm (27mm after wire tip 2mm cut)
Applicable seal	Round type seal (Outer diameter max φ10mm , Wire tip to bottom of seal 15mm or less)
Stripping length	2.0~7.0mm
Crimping capacity	19,600N : LPC220S (2.0TON equivalent) , Option 24,500N : SBN250S (2.5TON equivalent)
Detections	Strip error detector , Seal error , Low air pressure .
Electrical Connection	3phase AC200V±20V 50/60Hz 10A
Pneumatic System	0.5Mpa(5kgf/cm ²) approx. 150NL/min (Use clean dry air)
Dimensions	700W × 700D × 1,500H approx. 360kg
Options	Wire tip detector , F type guide, Terminal paper winding device , Crimping force device , SBM250S, Crimp error , Other brand APL conversion KIT, 40mm stroke applicator , Carrier cutter , 2 head applicator changer , Bad part cutter (Wire chopper) , Parts feeder , Drum feeder , Safety cover.

※J.A.M reserves the right to change specification without any prior notice.

◆ Proper ground required.